


















TYPE: Tacoma
MODEL: 2nd Generation - TRN/GRN 240, 245, 250
YEAR: 2005 to 2015
DETAIL: 4x4 Single Cab, Extra Cab, Dual Cab



| FRONT | | QTY | PART NUMBER | PRICE |
|---------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----|-------------------|-------|
| COIL SPRING | | | | |
| Single Cab 2.7L | | | | |
|  | Linear Rate Raised Height (45mm Lift) | 1 | C59-238 | B |
|  | Linear Rate Raised Height (50mm Lift) 80-100Kg | 1 | C59-300 | B |
| Dual Cab 4.0L | | | | |
|  | Linear Rate Raised Height (40mm Lift) | 1 | C59-302 | B |
|  | Linear Rate Raised Height (45mm Lift) 80-100Kg | 1 | C59-314 | B |
| SHOCK ABSORBER | | | | |
|  | Twin Tube Gas Heavy Duty | 2 | GS59-221 | |
|  | Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Original Setting of X = 213mm / 8.38" | 2 | MR59-50221 | |
| X - Centre of Eye to Spring Seat | | | | |
| STRUT CAP | | | | |
|  | Strut Top Cap | 2 | SC59-001 | |
| UPPER CONTROL ARM KIT | | | | |
| | (Pair) 3° Castor Built In Rubber Bushes with Ball Joint | 1 | UCA59-003K | |
| Must Fit When Raising Vehicle Above 50mm To Allow For Improved Caster Angle Alignment | | | | |
| BUMP STOP | | | | |
| | Replacement Bump Stop Progressive Adjustable 0-25mm Extension | 2 | BS59-560 | |
| Replaces Original Bump Stop. If Exceeding Listed Spring Seat Heights This MUST Be Used To Prevent Coil Bind. | | | | |

| REAR | | QTY | PART NUMBER | PRICE |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-----|--------------------|-------|
| LEAF SPRING | | | | |
|  | 3 + 2 Leaves Raised Height (55mm Lift) Medium Duty Up to 100Kg Constant Load | 2 | L59-110-R | |
|  | 4 + 2 Leaves Raised Height (55mm Lift) Heavy Duty 280Kg Constant Load | 2 | L59-111-R | |
|  | 5 + 2 Leaves Raised Height (55mm Lift) 400-550Kg Constant Load | 2 | L59-112-R | |
| SHACKLE BUSH KIT | | | | |
|  | Kit Contains: 6 x PB59-1503 | 1 | PB59-1101K | |
| U-BOLT KIT | | | | |
|  | Kit Contains: 2 x UB59-453-2 | 2 | UB59-453-2K | |
| SHOCK ABSORBER | | | | |
|  | Twin Tube Gas Heavy Duty | 2 | GS59-940 | |
|  | Monotube Remote Reservoir Heavy Duty | 2 | MR59-50940 | |
| PIN | | | | |
|  | Greasable: Fit in Pairs | 2 | SP59-060 | |